GMF
Group for Molecular Engineering of Functional Materials

2D Perovskite as a Hole Transporting Material for Efficient and Stable Perovskite Solar Cells

Hobeom Kim

18. 07. 2019

EPFL

Metal-Halide Perovskite

Unit Cell of Metal-Halide Perovskite



Crystal Structure of Metal-Halide Perovskite



AMX_3

A: Organic Ammonium or Alkali Metal (Cs, Rb and K)
M: Metal (Pb, Sn)
X: Halide (I, Br, Cl)

Perovskite as a Light Absorber





C. Ballif et al., *J. Phys. Chem. Lett.*, 5, 1035 (2014)
T. C. Sum et al., *Science*, 342, 344 (2013)

- ✓ Broad absorption.
- ✓ High absorption coefficient
- ✓ Long diffusion length
- ✓ High mobility of charge carriers

Limitation in 3D Perovskites





Y. Yan et al., *Adv. Mater.*, 26, 4653 (2014)
A. Petrozza and F. Angelis et al., *Energy Environ. Sci.*, 11, 702 (2018)



M. K. Nazeeruddin et al., *Nature Rev. Mater.*, 4, 4 (2019)

- ✓ Defects and trap states
  - → Non-radiative recombination
  - → Degradation of device efficiency



H. Snaith et al., *Nature Energy, 2*, 17135 (2017)

- ✓ ***Incorporation of 2D perovskite can lead to passivation of defect and reduction of density of trap states.***



A. Ho-Baillie et al., *ACS Energy Lett.*, 3, 647 (2018)

Limitation in Organic HTMs



Spiro-OMeTAD



PTAA





N.-G. Park et al., *ACS Appl. Mater. Interfaces*, 9, 7148 (2017)
J. Seo et al., *Adv. Sci.*, 6, 1900528 (2019)

✓ Pros

- Good solubility
- Reasonably high hole mobility
- Easy processability
- Favourable energetic configuration

✓ Cons

- **Necessary to use dopants to improve charge mobility**
  → Degradation of devices
- **Hygroscopic dopant**
- **High cost**
- **Complex multi-step synthesis and purification processes**

2D Perovskite as an HTL for Solar Cells

The dual role of the 2D perovskite

as an HTL and a passivation layer







Benzylammonium iodide

M. K. Nazeeruddin et al., *Energy Environ. Sci.*, 10, 621 (2017)

2D Perovskite as an HTL for Solar Cells

➢ Characterization of 2D Perovskite













The formation of 2D perovskite was c onfirmed with various characterizatio ns.

$$2PbI_2 + 2BnA^+ + Z^+ + 3X^-$$

$$\rightarrow BnA_2ZPbX_7$$

Z is a combination of FA, MA and Cs.

To be submitted

2D Perovskite as an HTL for Solar Cells

- Film morphology of perovskites





- Study on chemical bonds (XPS)



To be submitted

2D Perovskite as an HTL for Solar Cells

➢ Orientation of 2DP Perovskite (GIXD)





➢ UPS







To be submitted

2D Perovskite as an HTL for Solar Cells

- Trap passivation and hole current (mobility)







$$V_{\mathrm{TFL}} = n_{\mathrm{t}} \frac{eL^2}{2\varepsilon\varepsilon_0} \qquad J = \frac{9\varepsilon\varepsilon_0 \mu_h V^2}{8L^3}$$

	V_{TFL}[V]	n_{t}[cm^{-3}]	μ_{h}[cm^2/V·s]
w/o 2DP HTL	0.418	6.02×10^{15}	0.1135
w/ 2DP HTL	0.198	2.43×10^{15}	0.6469

To be submitted

2D Perovskite as an HTL for Solar Cells

➢ Photovoltaic characteristics









w/o 2DP HTL	***w/ 2DP HTL***
V_{oc} = 0.737 V	**V_{oc} = 0.940 V**
J_{sc} = 19.92 mA/cm^2	**J_{sc} = 23.29 mA/cm^2**
FF = 35.3 %	**FF = 68.5 %**
PCE = 5.19 %	**PCE = 15.0 %**

To be submitted

Conclusion



2D perovskite can function as an effective HTL and also a passivating layer.

The random orientation of the 2DP HTL can facilitate hole transport.

The 2DP HTL significantly increased PCE and extended the operational lifetime.

To be submitted

Acknowledgement

GMF
Group for Molecular Engineering of Functional Materials

Thank you for attention

EPFL

Group for Molecular Engineering of Functional Materials (GMF)

Apolo

This project has received funding from the Europea n Union's Horizon 2020 research and innovation pr ogramme under grant agreement No 763989.

INHA UNIVERSITY 1954

Prof. Hoichang Yang,
Mr. Mingyuan Pei